

**Dialog DataStar**[options](#)[logout](#)[feedback](#)[help](#)[databases](#)[easy search](#)**Advanced Search:****Inspec - 1898 to date (INZZ)**[limit](#)

Search history:

No.	Database	Search term	Info added since	Results	
1	INZZ	buffer NEAR cach\$ WITH (extent OR extents) WITH database\$	unrestricted	0	-
2	INZZ	database\$	unrestricted	136246	<a href="#">show titles</a>
3	INZZ	2 AND buffer NEAR cach\$	unrestricted	36	<a href="#">show titles</a>
4	INZZ	3 AND (extent OR extents)	unrestricted	0	-
5	INZZ	buffer NEAR cach\$	unrestricted	374	<a href="#">show titles</a>
6	INZZ	5 AND (extent OR extents)	unrestricted	2	<a href="#">show titles</a>
7	INZZ	6 AND (page OR pages)	unrestricted	0	-
8	INZZ	5 AND (page OR pages)	unrestricted	39	<a href="#">show titles</a>
9	INZZ	8 AND database\$	unrestricted	10	<a href="#">show titles</a>
10	INZZ	9 AND table\$	unrestricted	0	-

[hide](#) | [delete all search steps...](#) | [delete individual search steps...](#)Enter your search term(s): [Search tips](#) ☐ Thesaurus mapping Information added since:  or:   
(YYYYMMDD)[search](#)☐ Documents with images

Select special search terms from the following list(s):

- ☒ Publication year 1950-
- ☒ Publication year 1898-1949
- ☒ Inspec thesaurus - browse headings A-G
- ☒ Inspec thesaurus - browse headings H-Q
- ☒ Inspec thesaurus - browse headings R-Z

10/ 762,782

## Dialog DataStar

options

logout

feedback

help

databases

search  
page

titles

## Document

Select the documents you wish to save or order by clicking the box next to the document, or click the link above the document to order directly.

save

locally as: PDF document

search strategy:

do not include the search strategy

order

☒ Select All1 A page fault equation for modeling the effect of memory size.2 A self-tuning page cleaner for DB2.3 VLRU: buffer management in client-server systems.4 Integrating reliable memory in databases.5 An analytical study of object identifier indexing.6 Integrating reliable memory in databases.7 Multimedia support for databases.8 Holding a page: enhanced page level access control for database system9 ARIES/CSA: a method for database recovery in client-server architec10 Data base recovery in shared disks and client-server architectures.☒ document 1 of 10 [Order Document](#)

Inspec - 1898 to date (INZZ)

## Accession number &amp; update

0008805190 20060313.

## Title

A page fault equation for modeling the effect of memory size.

## Source

Performance Evaluation, {Perform-Eval-Netherlands}, Feb. 2006, vol. 63, no. 2, p. 99-130, 48 refs, CODEN: PEEVD9, ISSN: 0166-5316.

Publisher: Elsevier, Netherlands.

## Author(s)

Tay-Y-C, Min-Zou.





## Author affiliation

Tay, Y.C., Min Zou, Nat. Univ. of Singapore, Singapore.

## Abstract

Modeling the effect of memory size on **page** faults is very difficult, because they are the result of the interaction between process reference behavior and **page** replacement policy. Moreover, a change in memory size will alter the timing and pattern of references in a multiprogramming mix. This paper presents an equation to model how memory size affects **page** faults. The equation is derived with the help of a conjectured invariant on the interaction between reference behavior and replacement policy. The **page** fault equation is validated in several experiments with real applications and systems. The equation can be used for energy conservation and capacity planning, characterizing the memory requirement of software and managing memory allocation, modeling of processor **cache** misses and **database buffer** management. (All rights reserved Elsevier).

## Descriptors

 CACHE-STORAGE;  ENERGY-CONSERVATION;  PAGED-STORAGE;  RANDOM-ACCESS-

STORAGE; RESOURCE-ALLOCATION; STORAGE-ALLOCATION.

**Classification codes**

C6120 File-organisation\*;

C6150N Distributed-systems-software.

**Keywords**

**page-fault-equation;** process-reference-behavior; **page-replacement-** policy; multiprogramming; memory-size; energy-conservation; capacity-planning; memory-requirement; memory-allocation; **database-buffer-** management; power-control; **processor-cache-design-modelling.**

**Treatment codes**

P Practical.

**Language**

English.

**Publication type**

Journal-paper.

**Availability**

SICI: 0166-5316(200602)63:2L:99:PFEM; 1-9.

Publisher identity number: S0166-5316(05)00018-0.

**Digital object identifier**

10.1016/j.peva.2005.01.007.

**Publication year**

2006.

**Publication date**

20060200.

**Edition**

2006010.

**Copyright statement**

Copyright 2006 IEE.

COPYRIGHT BY The IET, Stevenage, UK

---

☒ **document 2 of 10** Order Document

**Inspec - 1898 to date (INZZ)**

**Accession number & update**

0007597206 20051201.

**Title**

A self-tuning **page** cleaner for DB2.

**Conference information**

Proceedings 10th IEEE International Symposium on Modeling, Analysis, and Simulation of Computer and Telecommunications Systems. MASCOTS 2002, Fort Worth, TX, USA, 11-16 Oct. 2002.

Sponsor(s): IEEE Computer. Soc. Tech. Committee on Computer Architecture; IEEE Comput. Soc. Tech. Committee on Simulation; ACM SIGSIM; ACM SIGARCH.

**Source**

Proceedings 10th IEEE International Symposium on Modeling, Analysis, and Simulation of Computer and Telecommunications Systems. MASCOTS 2002, 2002, p. 81-9, 8 refs, pp. xvi+521, ISBN: 0-7695-1840-0.

Publisher: IEEE Comput. Soc, Los Alamitos, CA, USA.

**Author(s)**

Wenguang-Wang, Bunt-R.

Editor(s): Boukrehche-A, Das-S-K, Majumdar-S.

**Author affiliation**

Wenguang Wang, Bunt, R., Dept. of Comput. Sci., Saskatchewan Univ., Saskatoon, Sask., Canada.

**Abstract**

The **buffer** pool in a DBMS is used to **cache** the disk **pages** of the **database**. Because typical **database** workloads are I/O-bound, the effectiveness of the **buffer** pool management algorithm is a crucial factor in the performance of the DBMS. In IBM's DB2 **buffer** pool, the **page** cleaning algorithm

is used to write changed **pages** to disks before they are selected for replacement. We conducted a detailed study of **page** cleaning in DB2 version 7.1.0 for Windows by both trace-driven simulation and measurements. Our results show that system throughput can be increased by 19% when the **page** cleaning algorithm is carefully tuned. In practice, however the manual tuning of this algorithm is difficult. A self-tuning algorithm for **page** cleaning is proposed posed in this paper to automate this tuning task. Simulation results show that the self-tuning algorithm can achieve performance comparable to the best manually tuned system.

**Descriptors**

 CACHE-STORAGE;  DATABASE-MANAGEMENT-SYSTEMS.

**Classification codes**

C6160 Database-management-systems-DBMS\*;

C6120 File-organisation.

**Keywords**

**self-tuning-page-cleaner**; IBM; **DB2-buffer-pool**; DBMS; **disk-pages- cache**; I/O-bound-workloads; **buffer-pool-management-algorithm**; **page- cleaning-algorithm**; DB2-version-7.1.0; Windows; trace-driven-simulation; system-throughput; manual-tuning; self-tuning-algorithm; simulation-results.

**Treatment codes**

A Application;

P Practical;

X Experimental.

**Language**

English.

**Publication type**

Conference-proceedings.

**Availability**

CCCC: 1526-7539/02/\$17.00.

**Digital object identifier**

10.1109/MASCOT.2002.1167063.

**Publication year**

2002.

**Publication date**

20020000.

**Edition**

2003016.

**Copyright statement**

Copyright 2003 IEE.

COPYRIGHT BY The IET, Stevenage, UK

---

 **document 3 of 10** Order Document

**Inspec - 1898 to date (INZZ)**

**Accession number & update**

0006720999 20051201.

**Title**

VLRU: **buffer** management in client-server systems.

**Source**

IEICE Transactions on Information and Systems, {IEICE-Trans-Inf-Syst-Japan}, June 2000, vol. E83-D, no. 6, p. 1245-54, 22 refs, CODEN: ITISEF, ISSN: 0916-8532.

Publisher: Inst. Electron. Inf. & Commun. Eng, Japan.

**Author(s)**

Sung-Jin-Lee, Chin-Wan-Chung.





**Author affiliation**

Sung-Jin Lee, Dept. of Inf. & Commun. Eng., Korea Adv. Inst. of Sci. & Technol., Seoul, South Korea.

**Abstract**

In a client-server system, when LRU or its variant **buffer** replacement strategy is used on both the client and the server, the **cache** performance on the server side is very poor mainly because of **pages** duplicated in both systems. This paper introduces a server **buffer** replacement strategy which uses a replaced **page-id** rather than a request **page-id**, for the primary information for its operations. The importance of the corresponding **pages** in the server **cache** is decided according to the replaced **page-ids** that are delivered from clients to the server, so that locations of the **pages** are altered. Consequently, if a client uses LRU as its **buffer** replacement strategy, then the server **cache** is seen by the client as a long virtual client LRU **cache** extended to the server. Since the replaced **page-id** is only sent to the server by piggybacking whenever a new **page** fetch request is sent, the operation to deliver the replaced **page-id** is simple and induces a minimal overhead. We show that the proposed strategy reveals good performance characteristics in diverse situations, such as single and multiple clients, as well as with various access patterns.

**Descriptors**

 CACHE-STORAGE;  CLIENT-SERVER-SYSTEMS;  DATABASE-MANAGEMENT-SYSTEMS;  
 PAGED-STORAGE.

**Classification codes**

C6120 File-organisation\*;  
C6150N Distributed-systems-software;  
C6160 Database-management-systems-DBMS.

**Keywords**

client-server-system; VLRU; **buffer-management**; **buffer-replacement- strategy**; **cache-performance**; **server-buffer-replacement-strategy**; **replaced-page-id**; **server-cache**; **pages**; **long-virtual-client-LRU-cache**; piggybacking; **page-fetch-request**; multiple-clients; single-clients; access-patterns.

**Treatment codes**

P Practical.

**Language**

English.

**Publication type**

Journal-paper.

**Availability**

SICI: 0916-8532(200006)E83D:6L.1245:VBMC; 1-Z.

**Publication year**

2000.

**Publication date**

20000600.

**Edition**

2000039.

**Copyright statement**

Copyright 2000 IEE.

COPYRIGHT BY The IET, Stevenage, UK

---

☒ **document 4 of 10** Order Document

**Inspec - 1898 to date (INZZ)**

**Accession number & update**

0006225485 20051201.

**Title**

Integrating reliable memory in **databases**.

**Conference information**

Proceedings of VLDB 97: 23rd International Conference on Very Large **Databases**, Athens, Greece, 26-29 Aug. 1997.

**Source**

Proceedings of the Twenty-Third International Conference on Very Large **Databases**, 1997, p. 76-85, 41 refs, pp. xvi+599, ISBN: 1-55860-470-7.

Publisher: Morgan Kaufmann Publishers, San Francisco, CA, USA.

**Author(s)**

Wee-Teck-Ng, Chen-P-M.

Editor(s): Jarke-M, Carey-M, Dittrich-K-R, Lockovsky-E, Loucopoulos-P, Jeusfeld-M-A.

**Author affiliation**

Wee Teck Ng, Chen, P.M., Dept. of Electr. Eng. & Comput. Sci., Michigan Univ., Ann Arbor, MI, USA.

**Abstract**

Recent results in the Rio project at the University of Michigan show that it is possible to create an area of main memory that is as safe as disk from operating system crashes. This paper explores how to integrate the reliable memory provided by the Rio file **cache** into a **database** system. We propose three designs for integrating reliable memory into **databases**: non-persistent **database buffer cache**, persistent **database buffer cache**, and persistent **database buffer cache** with protection. Non-persistent **buffer caches** use an I/O interface to reliable memory and require the fewest modifications to existing **databases**. However, they waste memory capacity and bandwidth due to double buffering. Persistent **buffer caches** use a memory interface to reliable memory by mapping it into the **database** address space. This places reliable memory under complete **database** control and eliminates double buffering, but it may expose the **buffer cache** to **database** errors. Our third design reduces this exposure by write protecting the **buffer pages**. Extensive fault tests show that mapping reliable memory into the **database** address space does not significantly hurt reliability. This is because wild stores rarely touch dirty, committed **pages** written by previous transactions. As a result, we believe that **databases** should use a memory interface to reliable memory.

**Descriptors**

 CACHE-STORAGE;  DATABASE-MANAGEMENT-SYSTEMS;  FAULT-TOLERANT-COMPUTING.

**Classification codes**

C6160 Database-management-systems-DBMS\*;

C6120 File-organisation;

C5470 Performance-evaluation-and-testing.

**Keywords**

reliable-memory; **databases**; **Rio-file-cache**; **database-system**; **database- buffer-cache**; **persistent-database-buffer-cache**; **persistent-database- buffer-cache-with-protection**; **buffer-cache**; **database-errors**.

**Treatment codes**

P. Practical.

**Language**

English.

**Publication type**

Conference-proceedings.

**Publication year**

1997.

**Publication date**

19970000.

**Edition**

1999016.

**Copyright statement**

Copyright 1999 IEE.

COPYRIGHT BY The IET, Stevenage, UK

---

☒ **document 5 of 10** [Order Document](#)

**Inspec - 1898 to date (INZZ)**

**Accession number & update**

0006147207 20051201.

**Title**

An analytical study of object identifier indexing.

**Conference information**

**Database** and Expert Systems Applications. 9th International Conference, DEXA '98. Proceedings, Vienna, Austria, 24-28 Aug. 1998.

Sponsor(s): Univ. Vienna; Faculty of Law; DEXA-Assoc; OCG (Austrian Comput. Soc.); GI (Gesellschaft für Informatik); et al.

#### Source

**Database** and Expert Systems Applications. 9th International Conference, DEXA'98. Proceedings, 1998, p. 38-49, 14 refs, pp. xvi +905, ISBN: 3-540-64950-6.

Publisher: Springer-Verlag, Berlin, Germany.

#### Author(s)

Norvag-K, Bratbergsengen-K.

Editor(s): Quirchmayr-G, Schweighofer-E, Bench-Capon-T-J-M.

#### Author affiliation

Norvag, K., Bratbergsengen, K., Dept. of Comput. & Inf. Sci., Norwegian Univ. of Sci. & Technol., Trondheim, Norway.

#### Abstract

To avoid OID index retrieval becoming a bottleneck, efficient buffering strategies are needed to minimize the number of disk accesses. In this paper, we develop analytical cost models which we use to find optimal sizes of the index **page buffer** and the index entry **cache**, for different memory sizes, index sizes, and access patterns. Because existing **buffer hit estimation models** are not applicable for index **page buffering** in the case of tree based indexes, we have also developed an analytical model for index **page buffer** performance. The cost gain from using the results in this paper is typically in the order of 200-300%. Thus, the results should be of valuable use in optimizers and tools for configuration and tuning of object-oriented **database** systems.

#### Descriptors

☞ CACHE-STORAGE; ☞ DATABASE-INDEXING; ☞ DATABASE-THEORY; ☞ OBJECT-ORIENTED-DATABASES; ☞ QUERY-PROCESSING; ☞ TREE-DATA-STRUCTURES.

#### Classification codes

C61601 Object-oriented-databases\*;

C6120 File-organisation;

C4250 Database-theory.

#### Keywords

object-identifier-indexing; OID-index-retrieval; efficient-buffering-strategies; minimized-disk-accesses; analytical-cost-models; optimal- **index-page-buffer-size**; **optimal-index-entry-cache-size**; memory-sizes; index-sizes; access-patterns; **buffer-hit-estimation-models**; tree-based-indexes; **index-page-buffer-performance**; cost-gain; optimizers; tools; configuration; tuning; **object-oriented-database-systems**.

#### Treatment codes

I Theoretical-or-mathematical.

#### Language

English.

#### Publication type

Conference-proceedings.

#### Publication year

1998.

#### Publication date

19980000.

#### Edition

1999004.

#### Copyright statement

Copyright 1999 IEE.

COPYRIGHT BY The IET, Stevenage, UK

☒ **document 6 of 10** Order Document

**Inspec - 1898 to date (INZZ)**

**Accession number & update**

0006101585 20051201.

**Title**Integrating reliable memory in **databases**.**Source**

VLDB Journal, {VLDB-J-Germany}, Aug. 1998, vol. 7, no. 3, p. 194-204, 48 refs, CODEN: VLDBFR, ISSN: 1066-8888.

Publisher: Springer-Verlag, Germany.

**Author(s)**Wee-Teck-Ng, Chen-P-M.**Author affiliation**

Wee Teck Ng, Chen, P.M., Div. of Comput. Sci. &amp; Eng., Michigan Univ., Ann Arbor, MI, USA.

**Abstract**

Results in the Rio project at the University of Michigan show that it is possible to create an area of main memory that is as safe as disk from operating system crashes. This paper explores how to integrate the reliable memory provided by the Rio file **cache** into a **database** system. Prior studies have analyzed the performance benefits of reliable memory; we focus instead on how different designs affect reliability. We propose three designs for integrating reliable memory into **databases**: non-persistent **database buffer cache**, persistent **database buffer cache**, and persistent **database buffer cache** with protection. Non-persistent **buffer caches** use an I/O interface to reliable memory and require the fewest modifications to existing **databases**. However, they waste memory capacity and bandwidth due to double buffering. Persistent **buffer caches** use a memory interface to reliable memory by mapping it into the **database** address space. This places reliable memory under complete **database** control and eliminates double buffering, but it may expose the **buffer cache** to **database** errors. Our third design reduces this exposure by write protecting the **buffer pages**. Extensive fault tests show that mapping reliable memory into the **database** address space does not significantly hurt reliability. This is because wild stores rarely touch dirty, committed **pages** written by previous transactions. As a result, we believe that **databases** should use a memory interface to reliable memory.

**Descriptors**

 CACHE-STORAGE;  OPERATING-SYSTEMS-COMPUTERS;  SOFTWARE-PERFORMANCE-EVALUATION;  SOFTWARE-RELIABILITY;  VERY-LARGE-DATABASES.

**Classification codes**C6160Z Other-DBMS\*;C6110B Software-engineering-techniques;C6120 File-organisation.**Keywords**

reliable-memory; **databases**; Rio-project; University-of-Michigan; main-memory; operating-system-crash; **file-cache**; performance-benefits; **nonpersistent-database-buffer-cache**; **persistent-database-buffer-cache**; input-output-interface; memory-capacity; double-buffering; memory-interface.

**Treatment codes**P Practical.**Language**

English.

**Publication type**Journal-paper.**Availability**

SICI: 1066-8888(199808)7:3L:194:IRMD; 1-L.

CCCC: 1066-8888/98/\$2.00+0.20.

**Publication year**

1998.

**Publication date**

19980800.

**Edition**

1998048.

**Copyright statement**

Copyright 1998 IEE.



☒ **document 7 of 10** [Order Document](#)

**Inspec - 1898 to date (INZZ)**

**Accession number & update**

0005871118 20051201.

**Title**

Multimedia support for **databases**.

**Conference information**

Proceedings of the Sixteenth ACM SIGACT-SIGMOD-SIGART Symposium on Principles of **Database** Systems, PODS 1997, Tucson, AZ, USA, 12-14 May 1997.

Sponsor(s): ACM.

**Source**

Proceedings of the Sixteenth ACM SIGACT-SIGMOD-SIGART Symposium on Principles of **Database** Systems, PODS 1997, 1997, p. 1-11, 38 refs, pp. viii+268, ISBN: 0-89791-910-6.

Publisher: ACM, New York, NY, USA.

**Author(s)**

[Ozden-B](#), [Rastogi-R](#), [Silberschatz-A](#).











**Author affiliation**

Ozden, B., Rastogi, R., Silberschatz, A., AT&T Bell Labs., Murray Hill, NJ, USA.

**Abstract**

Next-generation **database** systems will need to provide support for both textual data and other types of multimedia data (e.g. images, video, audio). These two types of data differ in their characteristics, and hence require different techniques for their organization and management. For example, continuous-media data (e.g. video, audio) requires a guaranteed transfer rate. In this paper, we provide an overview of (1) how **database** systems can be architected to support multimedia data, and (2) the main challenges in devising new algorithms to manage multimedia data. In order to provide rate guarantees for continuous-media data, an admission control scheme must be employed that determines, for each client, whether there are sufficient resources available to service that client. To maximize the number of clients that can be admitted concurrently, the various system resources must be allocated and scheduled carefully. In terms of disks, we use algorithms for retrieving/storing data from/to disks that reduce the seek latency time and eliminate rotational delay, thereby providing high throughput. In terms of main memory, we use **buffer** management schemes that exploit the sequential access patterns for continuous-media data, thereby resulting in efficient replacement of **buffer pages** from the **cache**. In addition to discussing resource scheduling, we also present schemes for the storage layout of data on disks and schemes that provide fault tolerance by ensuring uninterrupted service in the presence of disk failures.

**Descriptors**

 [CACHE-STORAGE](#);  [CLIENT-SERVER-SYSTEMS](#);  [CONCURRENCY-CONTROL](#);  
 [DISTRIBUTED-DATABASES](#);  [FAULT-TOLERANT-COMPUTING](#);  [INFORMATION-STORAGE](#);  
 [MULTIMEDIA-COMPUTING](#);  [PAGED-STORAGE](#);  [RESOURCE-ALLOCATION](#);  
 [SCHEDULING](#).

**Classification codes**

[C6160B Distributed-databases\\*](#);  
[C6120 File-organisation](#);  
[C6130M Multimedia](#);  
[C6160S Spatial-and-pictorial-databases](#).

**Keywords**

multimedia-support; **database-systems**; textual-data; continuous-media-data; guaranteed-transfer-rate; **database-system-architecture**; multimedia-data-management-algorithms; admission-control-scheme; resource-determination; concurrent-client-number-maximization; system-resource-allocation; resource-scheduling; disk-storage; data-retrieval; seek-latency-time; rotational-delay; throughput; main-memory; **buffer-management-schemes**; sequential-access-patterns; **buffer- page-replacement**; **cache**; data-storage-layout; fault-tolerance; uninterrupted-service; disk-failures.

**Treatment codes**

P. Practical.

**Language**

English.

**Publication type**

Conference-proceedings.

**Availability**

CCCC: 0 89791 910 6/97/05..\$3.50.

**Publication year**

1997.

**Publication date**

19970000.

**Edition**

1998012.

**Copyright statement**

Copyright 1998 IEE.

COPYRIGHT BY The IET, Stevenage, UK

---

☒ **document 8 of 10** Order Document

**Inspec - 1898 to date (INZZ)**

**Accession number & update**

0005219986 20051201.

**Title**

Holding a **page**: enhanced **page** level access control for **database** systems.

**Conference information**

ADC'96. Seventh Australasian **Database** Conference, Melbourne, Vic., Australia, 29-30 Jan. 1996.

**Source**

Australian Computer Science Communications, {Aust-Comput-Sci-Commun-Australia}, 1996, vol. 18, no. 2, p. 38-47, 16 refs, CODEN: ACSCDD, ISSN: 0157-3055.

Publisher: James Cook Univ, Australia.

**Author(s)**

Harris-E-P, Ramamohanarao-K.








**Author affiliation**

Harris, E.P., Ramamohanarao, K., Dept. of Comput. Sci., Melbourne Univ., Parkville, Vic., Australia.

**Abstract**

A new scheme for physically accessing tuples by multiple transactions is described for **database** systems using a shared-memory **buffer cache**. Using this scheme, a transaction must first obtain logical permission to access a tuple, e.g. by taking a lock on the tuple. Once logical permission has been granted, a **page-level** latch is taken for the initial physical access to the tuple. However, by the introduction of a new primitive (**<b>hold</b>**) into the latching system, which ensures that the tuple is not moved, a latch on the **page** is not required to subsequently read the tuple. This brings the physical level of concurrency closer to the logical level of concurrency. Our scheme is compared with other schemes which can be used for access control.

**Descriptors**

 AUTHORISATION;  CACHE-STORAGE;  CONCURRENCY-CONTROL;  DATABASE-MANAGEMENT-SYSTEMS;  PAGED-STORAGE;  SHARED-MEMORY-SYSTEMS;  TRANSACTION-PROCESSING.

**Classification codes**

C6120 File-organisation\*;

C6130S Data-security;

C6160 Database-management-systems-DBMS.

**Keywords**

**page-holding**; **page-level-access-control**; **database-systems**; physical- tuple-access-scheme; multiple-transactions; **shared-memory-buffer- cache**; transaction; logical-permission; tuple-lock; **page-level-latch**; hold-primitive; concurrency.

**Treatment codes**

P Practical.

**Language**

English.

**Publication type**

Conference-proceedings; Journal-paper.

**Availability**

SICI: 0157-3055(1996)18:2L:38:HPEP; 1-0.

**Publication year**

1996.

**Publication date**

19960000.

**Edition**

1996012.

**Copyright statement**

Copyright 1996 IEE.

COPYRIGHT BY The IET, Stevenage, UK

---

☒ **document 9 of 10** Order Document

**Inspec - 1898 to date (INZZ)**

**Accession number & update**

0004726613 20051201.

**Title**

ARIES/CSA: a method for **database** recovery in client-server architectures.

**Conference information**

1994 ACM SIGMOD International Conference on Management of Data, Minneapolis, MN, USA, 24-27 May 1994.

Sponsor(s): ACM.

**Source**

SIGMOD Record, {SIGMOD-Rec-USA}, June 1994, vol. 23, no. 2, p. 55-66, 30 refs, CODEN: SRECD8, ISSN: 0163-5808, USA.

**Author(s)**

Mohan-C, Narang-I.






**Author affiliation**

Mohan, C., Narang, I., Data Base Technol. Inst., IBM Almaden Res. Center, San Jose, CA, USA.

**Abstract**

Presents an algorithm called ARIES/CSA (Algorithm for Recovery and Isolation Exploiting Semantics for Client-Server Architectures) for performing recovery correctly in client-server architectures where the server manages the disk version of the **database**. The clients, after obtaining **database pages** from the server, **cache** them in their **buffer** pools. Clients perform their updates on the **cached pages** and produce log records. The log records are buffered locally in virtual storage and later sent to the single log at the server. ARIES/CSA supports write-ahead logging, fine-granularity (e.g. record) locking, partial rollbacks and flexible **buffer** management policies like 'steal' and 'no-force'. It does not require that the clocks on the clients and the server be synchronized. Checkpointing by the server and the clients allows for flexible and easier recovery.

**Descriptors**

 BUFFER-STORAGE;  CLOCKS;  DISTRIBUTED-DATABASES;  SYSTEM-RECOVERY;  
 VIRTUAL-STORAGE.

**Classification codes**

C6160B Distributed-databases\*.

**Keywords**

ARIES/CSA; **database-recovery**; client-server-architectures; isolation; semantics; **database-disk-version**; **database-pages**; locally-buffered-log-records; **buffer-pools**; updates; **cached-pages**; virtual-storage; write-ahead-logging; fine-granularity-locking; record-locking; partial-rollbacks; **flexible-buffer-management-policies**; steal; no-force; clocks; checkpointing.

**Treatment codes**

P Practical.

**Language**

English.

**Publication type**

Conference-proceedings; Journal-paper.

**Availability**

CCCC: 0163-5808/94/0005\$3.50.

**Publication year**

1994.

**Publication date**

19940600.

**Edition**

1994030.

**Copyright statement**

Copyright 1994 IEE.

COPYRIGHT BY The IET, Stevenage, UK

☒ **document 10 of 10** Order Document

**Inspec - 1898 to date (INZZ)**

**Accession number & update**

0004468185 20051201.

**Title**

Data base recovery in shared disks and client-server architectures.

**Conference information**

Proceedings of the 12th International Conference on Distributed Computing Systems (Cat No.92CH3175-7), Yokohama, Japan, 9-12 June 1992.

Sponsor(s): IEEE; Inf. Process. Soc. Japan.

**Source**

Proceedings of the 12th International Conference on Distributed Computing Systems (Cat No.92CH3175-7), 1992, p. 310-17, 32 refs, pp. xxii+725, ISBN: 0-8186-2865-0.

Publisher: IEEE Comput. Soc. Press, Los Alamitos, CA, USA.

**Author(s)**

Mohan-C, Narang-I.

**Author affiliation**

Mohan, C., Narang, I., IBM Almaden Res. Center, San Jose, CA, USA.

**Abstract**

Solutions to the problem of performing recovery correctly in shared-disks (SD) and client-server (CS) architectures are presented. In SD, all the disks containing the data bases are shared among multiple instances of the **database** management system (DBMS). In CS, the server manages the disk version of the data base. The clients, after obtaining **database pages** from the server, **cache** them in their **buffer** pools. Clients perform their updates on the **cached pages** and produce log records. In write-ahead logging (WAL) systems, a monotonically increasing value called the log sequence number (LSN) is associated with each log record. Every **database page** contains the LSN of the log record describing the most recent update to that **page**. This is required for proper recovery after a system failure. A technique for generating monotonically increasing LSNs in SD and CS architectures without using synchronized clocks is presented.

**Descriptors**

 DATABASE-MANAGEMENT-SYSTEMS;  PERFORMANCE-EVALUATION.

**Classification codes**

C6160 Database-management-systems-DBMS\*;

C5470 Performance-evaluation-and-testing.

**Keywords**

**database-recovery;** shared-disks; client-server-architectures; data- bases; multiple-instances;  
**database-management-system;** **database-pages;** **buffer-pools;** **cached-pages;** log-records;  
write-ahead-logging; log- sequence-number.

**Treatment codes**

P Practical.

**Language**

English.

**Publication type**

Conference-proceedings.

**Availability**

CCCC: 0 8186 2865 0/92/\$3.00.

**Digital object identifier**

10.1109/ICDCS.1992.235026.

**Publication year**

1992.

**Publication date**

19920000.

**Edition**

1993032.

**Copyright statement**

Copyright 1993 IEE.

COPYRIGHT BY The IET, Stevenage, UK



locally as:

PDF document

search strategy:

do not include the search strategy



Top - News & FAQs - Dialog

© 2006 Dialog

**Dialog DataStar**[options](#)[logoff](#)[feedback](#)[help](#)[databases](#)[search  
page](#)[titles](#)

## Document

Select the documents you wish to [save](#) or [order](#) by clicking the box next to the document, or click the link above the document to order directly.

[next  
documents](#)[prev](#)locally as: [PDF document](#) search strategy: [do not include the search strategy](#)[order](#)☒ **document 1 of 2** [Order Document](#)**Inspec - 1898 to date (INZZ)****Accession number & update**

0008949474 20060625.

**Title**

Improving trace **cache** processor performance by trace **cache** hierarchy and path-based trace prefetch.

**Source**

Chinese Journal of Electronics, {Chin-J-Electron-China}, April 2006, vol. 15, no. 2, p. 231-6, 10 refs, CODEN: CHJEEW, ISSN: 1022-4653.

Publisher: Chinese Inst. Electron, China.

**Author(s)**

[Wang-Kaifeng](#), [Ji-Zhenzhou](#), [Hu-Mingzeng](#).




**Author affiliation**

Wang Kaifeng, Ji Zhenzhou, Hu Mingzeng, Sch. of Comput. Sci. & Technol., Harbin Inst. of Technol., China.

**Abstract**

The performance of trace **cache** processor rests with trace **cache** efficiency to a great **extent**. Higher trace **cache** miss rate will reduce performance significantly because only a low fetch-bandwidth can be maintained by conventional instruction **cache**. Unfortunately, with the ever increasing conventional application scale, higher trace **cache** miss rate is inevitable for the relative small capacity of trace **cache**, which will become the bottleneck of performance improvement. In this paper, we proposed trace **cache** hierarchy to remedy the limited capacity of 1-level trace **cache**. 2-level trace **cache** is incorporated in trace processors. But the simulation results show that only augmenting 2-level trace **cache** can not bring significant performance improvement for the long access latency. So we propose a path-based trace prefetch mechanism to reduce the latency of 2-level trace **cache** access further. Path-based trace prefetch mechanism is developed on top of next N trace prediction mechanism. By predicting the next N trace from current and prefetching it into trace prefetch **buffer** from 2-level trace **cache**, the access latency of 2-level trace **cache** can be reduced. The simulation results show that augmenting an 8K-Entry, eight-way 2-level trace **cache**, an 16-Entry trace prefetch **buffer** and prefetch distance set to 3, the average IPC improvement is 12.0% for eight SPECint95 benchmarks.

**Descriptors**

 [CACHE-STORAGE](#);  [MICROPROCESSOR-CHIPS](#);  [STORAGE-MANAGEMENT](#).

**Classification codes**

[B1265F Microprocessors-and-microcomputers\\*](#);  
[B1265D Memory-circuits](#);

C5130 Microprocessor-chips\*;  
C5320G Semiconductor-storage;  
C6120 File-organisation.

**Keywords**

**trace-cache-processor-performance; trace-cache-hierarchy; path-based- trace-prefetch; trace-cache-miss-rate; instruction-cache; trace-prediction-mechanism; trace-prefetch-buffer; access-latency.**

**Treatment codes**

P Practical.

**Language**

English.

**Publication type**

Journal-paper.

**Availability**

SICI: 1022-4653(200604)15:2L.231:ITCP; 1-5.

**Publication year**

2006.

**Publication date**

20060400.

**Edition**

2006025.

**Copyright statement**

Copyright 2006 The Institution of Engineering and Technology.

COPYRIGHT BY The IET, Stevenage, UK

next  
documents

save

locally as:

PDF document

search strategy:

do not include the search strategy

order

Top - News & FAQs - Dialog

© 2006 Dialog

## Dialog DataStar

options

logout

feedback

help

databases

search  
page

titles

## Document

Select the documents you wish to save or order by clicking the box next to the document, or click the link above the document to order directly.

previous  
documents

save

locally as: PDF document

search strategy: do not include the search strategy

order

☒ **document 2 of 2** [Order Document](#)
**Inspec - 1898 to date (INZZ)****Accession number & update**

0007685765 20051201.

**Title**

SANTopia: shared-disk file system for storage cluster.

**Conference information**

PDCS 2002: 14th IASTED International Conference on Parallel and Distributed Computing and Systems, Cambridge, MA, USA, 4-6 Nov. 2002.

Sponsor(s): IASTED.

**Source**

Proceedings of the 14th IASTED International Conference Parallel and Distributed Computing and Systems, 2002, p. 464-9, 13 refs, pp. vi +860, ISBN: 0-88986-366-0.

Publisher: ACTA Press, Anaheim, CA, USA.

**Author(s)**[Yong-Ju-Lee](#), [Choo-Seo-Park](#), [Gyoung-Bae-Kim](#), [Kee-Wok-Rim](#), [Bum-Joo-Shin](#).**Author affiliation**

Yong-Ju Lee, Choo-Seo Park, Gyoung-Bae Kim, Kee-Wok Rim, Dept. of Comput. Syst., Electron. &amp; Telecommun. Res. Inst., Daejeon, South Korea.

**Abstract**

There have been large storage demands for manipulating multimedia data such as images and video. To solve tremendous storage demands, one major research is the SAN (storage area network) that provides local file requests directly from shared disk storage and also eliminates server bottlenecks to performance and availability. The SAN also improves network latency and bandwidth through a new channel interface like FC (fibre channel). The FC is capable of maintaining several simultaneous gigabit data transfer, but to make use of an efficient storage network like SAN, a traditional file system is not adaptable in terms of scalability, availability and consistency issues. We propose a new shared-disk file system, the so-called SANTopia file system, for shared disk storage that manipulates large-scale inode objects and provides key cluster enabling technology for Linux, helping to bring the scalability, availability and load balancing benefits of clustering to Linux. We describe the architecture and design issues of a shared-disk file system for shared disk storage and provide the efficient bitmap, **extent-based** semi-flat structure and two-phase directory structure using extendible hashing. We also present a **cache** coherence protocol using a **buffer** forwarding scheme to maintain efficient metadata consistency. We evaluate the performance in terms of average response time and I/O rate.

**Descriptors**
 [DISTRIBUTED-DATABASES](#);  [FILE-SERVERS](#);  [META-DATA](#);  [SHARED-MEMORY](#)



**SYSTEMS;****STORAGE-MANAGEMENT.****Classification codes**C6120 File-organisation\*;C6160B Distributed-databases.**Keywords**

SANtopia; shared-disk-file-system; storage-cluster; multimedia; data-manipulation; storage-area-network; shared-disk-storage; network-server; network-latency; network-bandwidth; FC; fibre-channel; gigabit-data-transfer; storage-network; Linux; load-balancing; two-phase-directory-structure; extendible-hashing; **cache-coherence-** protocol; **buffer-forwarding-scheme**; metadata-consistency; I/O-rate.

**Treatment codes**P Practical.**Language**

English.

**Publication type**Conference-proceedings.**Publication year**

2002.

**Publication date**

20020000.

**Edition**

2003027.

**Copyright statement**

Copyright 2003 IEE.

COPYRIGHT BY The IET, Stevenage, UK

previous documentssave

locally as: PDF document

search strategy: do not include the search strategy

order

Top - News &amp; FAQs - Dialog

© 2006 Dialog

# WEST Search History





DATE: Friday, August 04, 2006

Hide?	<u>Set</u> <u>Name</u>	<u>Query</u>	<u>Hit</u> <u>Count</u>
		<i>DB=PGPB,USPT,USOC; PLUR=NO; OP=OR</i>	
<input type="checkbox"/>	L55	(L53 or L54) and (search\$ or quer\$ or request\$ or inquir\$ or enquir\$ or question)	85
<input type="checkbox"/>	L54	L52 and ((extent or extents) near page\$)	2
<input type="checkbox"/>	L53	L52 and ((database\$ or (data adj1 base\$)) with table\$)	86
<input type="checkbox"/>	L52	(L50 or L51) and (buffer adj1 cach\$)	235
<input type="checkbox"/>	L51	(707/200  707/201  707/202  707/203  707/204  707/205).ccls.	7067
<input type="checkbox"/>	L50	(707/2  707/3  707/4).ccls.	9745
<input type="checkbox"/>	L49	L48 and engine\$	28
<input type="checkbox"/>	L48	L47 and (search\$ or quer\$ or request\$ or inquir\$ or enquir\$ or question)	28
<input type="checkbox"/>	L47	L46 and (buffer adj1 cach\$)	28
<input type="checkbox"/>	L46	(database adj1 engine\$)	2373
<input type="checkbox"/>	L45	L44 and engine\$	1
<input type="checkbox"/>	L44	20030041214.pn.	1
<input type="checkbox"/>	L43	L42 and (engine\$ near (search\$ or quer\$ or request\$ or inquir\$ or enquir\$ or question\$))	33
<input type="checkbox"/>	L42	(buffer adj1 cach\$)	2240
<input type="checkbox"/>	L41	L40 and (buffer near cach\$)	18
<input type="checkbox"/>	L40	L39 and (engine\$ near (search\$ or quer\$ or request\$ or inquir\$ or enquir\$ or question\$))	4198
<input type="checkbox"/>	L39	((database\$ or (data adj1 base\$)) with table\$)	53497
<input type="checkbox"/>	L38	L37 and ((database\$ or (data adj1 base\$)) with table\$)	16
<input type="checkbox"/>	L37	L36 and cach\$	97
<input type="checkbox"/>	L36	L35 and (engine\$ near (search\$ or quer\$ or request\$ or inquir\$ or enquir\$ or question\$))	203
<input type="checkbox"/>	L35	((extent or extents) with (page or pages))	3078
<input type="checkbox"/>	L34	L33 and (extent or extents)	2
<input type="checkbox"/>	L33	L31 and (buffer with cach\$)	15
<input type="checkbox"/>	L32	L31 and (buffer near cach\$)	1
<input type="checkbox"/>	L31	L30 and (engine\$ near (search\$ or quer\$ or request\$ or inquir\$ or enquir\$ or question\$))	1486
<input type="checkbox"/>	L30	(international adj1 business).asn.	63605
<input type="checkbox"/>	L29	2002198872.pn.	0

10/763, 752

<input type="checkbox"/>	L28	2002198872.pn.	0
<input type="checkbox"/>	L27	L26 and (engine\$ near (search\$ or quer\$ or request\$ or inquir\$ or enquir\$ or question\$))	17
<input type="checkbox"/>	L26	((extent or extents) near page\$)	201
<input type="checkbox"/>	L25	L16 and ((extent or extents) near page\$)	2
<input type="checkbox"/>	L24	L23 and page\$	11
<input type="checkbox"/>	L23	(L19 or L20) and ((database\$ or (data adj1 base\$)) with table\$)	11
<input type="checkbox"/>	L22	(L19 or L20) and (memory with (database\$ or (data adj1 base\$)) with table\$)	0
<input type="checkbox"/>	L21	L16 and (memory with (database\$ or (data adj1 base\$)) with table\$)	2
<input type="checkbox"/>	L20	L18 and (extent or extents).ab.	58
<input type="checkbox"/>	L19	L18 and (extent or extents).ti.	1
<input type="checkbox"/>	L18	(engine\$ near (search\$ or quer\$ or request\$ or inquir\$ or enquir\$ or question\$))	19038
<input type="checkbox"/>	L17	L16 and engine\$	1
<input type="checkbox"/>	L16	(buffer near cach\$ near (extent or extents))	2
<input type="checkbox"/>	L15	L5 and (search\$ or request\$ or inquir\$ or enquir\$ or question\$ or quer\$)	2
<input type="checkbox"/>	L14	L12 and page\$	1
<input type="checkbox"/>	L13	(L8 or L9 or L10) and engine\$	0
<input type="checkbox"/>	L12	L11 and engine\$	1
<input type="checkbox"/>	L11	L1 and ((search\$ or quer\$ or request\$ or inquir\$ or enquir\$ or question\$) near (extent or extents))	5
<input type="checkbox"/>	L10	L1 and ((extent or extents) same (buffer adj1 cach\$))	2
<input type="checkbox"/>	L9	L1 and ((extent or extents) with (buffer adj1 cach\$))	2
<input type="checkbox"/>	L8	L1 and ((extent or extents) near (buffer adj1 cach\$))	1
<input type="checkbox"/>	L7	L1 and ((search\$ or quer\$ or request\$ or inquir\$ or enquir\$ or question\$) with (extent or extents) with (buffer adj1 cach\$))	0
<input type="checkbox"/>	L6	L5 and engine\$	1
<input type="checkbox"/>	L5	L4 and (memory with (database\$ or (data adj1 base\$)) with table\$)	2
<input type="checkbox"/>	L4	L3 and (database\$ or (data adj1 base\$))	5
<input type="checkbox"/>	L3	((buffer adj1 cache) with (extent or extents))	10
<input type="checkbox"/>	L2	((buffer adj1 cache) near (extent or extents))	2

*DB=USPT; PLUR=NO; OP=OR*

(5317727 5812996 5822749 5758149 5794229 5794228 5655080 6374232  
6973452 6101497 6442551 6021426 5903898 5956705 6457020 6470330  
6243710 5668987 6073129 6105033 6122627 6134540 6226637 6226637  
6285997 6341281 6470344 6477527 6574639 6801905 6889234 5832508  
5737536 5826253 5850507 6182241 6898608 6957177 5201046 5511190  
5742806 5918225 6289334 5884303 6654752 6961729 7010308 6389513  
5787418 5842209).pn. (6078926 5426747 5940289 6125209 5581704 5615362  
5706506 5802524 5832475 5941947 5944780 5974129 5999946 6009271  
6070165 6122628 6128648 6134541 6185557 6279033 6282281 6360214  
6381627 6401090 6411966 6438562 6449657 6466570 6487641 6532490

6539382 6601062 6604096 6694306 6694322 6732117 6741997 6763357  
6898603 6950823 7062480 6728840 6912636 5799210 6230220 6591351  
6760824 6904503 6347312 6748386).pn. (6014655 6115705 5210870 5237661  
5454105 5530883 5537622 5537604 5537603 5548769 5590362 5619713  
5745915 5758146 5778353 6457000 6691101 6754825 6836845 5418940  
5802599 6049848 5907846 5010478 5283894 5542078 5781897 5918224  
6115703 6928451 5561778 5579499 5590319 5594881 5600831 5701460  
5737591 6134018 6253195 5506984 5694608 5893125 6138112 5317731  
5495606 5546576 5560007 5596744 5634053 5664173).pn. (5666528 5724570  
5412806 5603025 5692182 5692174 5727196 5787416 5845288 5870752  
5894311 5903887 5937401 5950188 6006224 6012064 6044370 6076092  
6081801 6212526 5201048 5265244 5329626 5367675 5423022 5504885  
5574900 5596745 5615337 5619688 5627959 5632015 5694591 5701456  
5701453 5749079 5761493 5761653 5774692 5794231 5797136 5799310  
5806066 5826077 5835904 5842197 5842196 5852821 5878426 5897622).pn. 297  
(5905982 5918232 5924089 5930795 5930764 5937415 5943666 5953715  
5956727 5960426 5966695 5974407 5974418 5987454 5991754 5995958  
5995957 5995973 6006214 6009265 6009428 6012054 6016488 6023695  
6023696 6026391 6044216 6047285 6047291 6078925 6081799 6085189  
6088694 6092061 6105025 6108647 6108648 6112198 6125360 6134543  
6134546 6138120 6148296 6192370 6199062 6199063 6212526 6249783  
6249791 6263339).pn. (6272487 6282547 6298342 6324533 6353826 6356889  
6363387 6381605 6421658 6427123 6430556 6453269 6460043 6470287  
6470335 6477525 6477540 6496819 6502088 6507834 6516310 6549907  
6557012 6560593 6571232 6581052 6581060 6584476 6598059 6615202  
6615206 6618719 6631386 6633882 6636846 6691166 6697818 6708179  
6708186 6714938 6732084 6735582 6735598 6741982 6748377 6757670  
6799184 6801850 6807546).pn.

END OF SEARCH HISTORY